

Tools, Tips, and Torches



MATERIAL HANDLING TOOLS



Hot Mastic Applicator #57650
Handles and distributes Mastic One® from Patcher II or 4 to repair area. Propane heated, left and right side discharge gate, 10-gallon capacity. Not intended for melting and mixing mastic.



Pour Pot with Wheels #40200
Use to apply a uniform band of sealant to a crack or joint. Wheeled for ease of use. Gravity feed with shut off lever.



Hand Held Pour Pot #40201
For application of thin crack sealant to a joint or crack. Gravity feed with shut off lever.



Mastic Transport Bucket #32263
Metal bucket for transporting Mastic One or TechCrete® from the Patcher II or 4 to the repair site. Has a 3 gallon capacity.



Heavy Duty Squeegee w/Aluminum Handle #27245
Use for leveling crack sealant and where a sealant overband is recommended.
Replacement Blade #27241
4" x 18" x 3/8"



Heavy Duty Squeegee w/Wooden Handle #27245W
Use for leveling crack sealant and where a sealant overband is recommended.
Replacement Blade #27241W
2" x 12-1/4" x 1/4"



Heavy Duty Compact Squeegee w/ Aluminum Handle - #27199
w/ Wooden Handle - #27199W
Use for leveling crack sealant and where a sealant overband is recommended.
Replacement Blade - #27195
2-1/2" x 17" x 3/8"

PATCHING TOOLS



Ironing Wand #32243

Moves and levels Mastic One® and TechCrete® in the repair area.



Chute Scraper #32246

Scrapes and cleans Mastic One and TechCrete from the inside of the Patcher walls and down the Patcher chute.



Tank Scraper #32258

Scrapes, cleans and removes Mastic One and TechCrete from the inside of the Patcher II & Patcher 4.



Shoe Box

Applies Mastic One and TechCrete to the repair. Fill by using the Patcher chute, Hot Mastic Applicator, or Mastic Bucket.

| | |
|---------|-----------|
| #58550N | 8"x4"x3" |
| #58540N | 8"x4"x6" |
| #32350 | 8"x8"x3" |
| #32255 | 8"x8"x6" |
| #32351 | 8"x10"x3" |
| #32250 | 8"x10"x6" |
| #32352 | 8"x12"x3" |
| #32252 | 8"x12"x6" |
| #32353 | 8"x14"x3" |
| #32253 | 8"x14"x6" |

SEALING TIPS



Drip Stopper

Use with Super Shot & EZ Series sealing tip. Stops sealant drip once wand trigger is released.

1. Tip Adapter #27114
2. Duckbill Valve #50270
3. Shroud - Tip Adapter #27115



Swivel Applicator

Use with Super Shot & EZ Series with or w/o Drip Stopper.

3" Swivel Applicator #27120
4" Swivel Applicator #27130



Duckbill #50270

Use with Super Shot & EZ Series wands to prevent dripping of material.



Applicator Disk

Used for overbanding, great labor saver.

3" Disk Assembly #27162
4" Disk Assembly #27163
6" Disk Assembly #27164



Round Sealing Tip

Multi-purpose random cracks and joints. Use with a squeegee for most applications.

Sealing tip assembly 3/8" #27170
Sealing tip assembly 1/2" #27171



Sealing Foot/Flush

Used for random asphalt and concrete cracks.

Sealing tip/ft assembly
1/4" flush #27154
Sealing tip/ft assembly
3/8" flush #27155



Sealing Foot/Protruded

Used for straight asphalt and concrete joints.

Sealing tip/ft assembly
1/4" protruding #27159
Sealing tip/ft assembly
3/8" protruding #27160



Joint Sealing Tip

Use for straight asphalt and concrete joints.

Sealing tip assembly 1/4" #27146
Sealing tip assembly 3/8" #27147

LANCES & TORCHES



Hand Torch

Torch fueled by LPG to provide a controlled flame to warm and dry pavement and to destroy vegetation within cracks.

20 ft. Hose #25012
12 ft. Hose #25016
50 ft. Hose #25021



Cold Air Lances

Uses cold compressed air to clean and remove debris from cracks and joints. Comes standard with a compressor on new melters.

Cold Air Lance #42648
(for use with 50-70 CFM compressors)
Cold Air Lance, High Output #47483N
(for use with 100 CFM compressors)



Hot Air Lance High-Velocity Kit

Uses hot compressed air to clean, dry, and remove debris from cracks and joints, delivering up to 2,600°F flameless hot air at 3,000 ft/second. Includes a lance, LPG regulator with gauge, air filter/water separator, wheel kit, and fittings.

40 ft. Hose #45650
60 ft. Hose #45660



Hot Air Lance Low-Velocity Kit #32259

Uses hot air to clean and dry, and remove debris from cracks and joints without a compressor. Includes a lance, 50' LPG hose, LPG regulator, and 1/2" standard air quick connect.